

## LUBEX MITRAS MT EP 75W-80

### HIGH PERFORMANCE MANUAL TRANSMISSION OIL

#### PRODUCT DESCRIPTION

It is a synthetic technology manual transmission oil developed to perform better than conventional GL-4 oils by using high quality base oils and specially selected additive package.

#### APPLICATION/USAGE

It is particularly recommended for use in manual transmissions of passenger cars, light commercial vehicles, and heavy-duty vehicles. It is also suitable for transaxles, transfer cases, and final drives requiring API GL-4 gear oil.

#### ADVANTAGES/BENEFITS

- Its thermal stability and high oxidation resistance provide superior protection against sludge and deposit formation and keep the equipment clean.
- Its superior resistance to aging helps extend oil change intervals and reduce maintenance costs.
- Its formulation, compatible with gaskets and seals, prevents oil leaks and increases equipment efficiency and reliability.
- Extends equipment life by providing protection against rust and corrosion.
- Excellent fluidity even at very low operating temperatures ensures smooth gear shifting and superior protection.
- Excellent foaming resistance prevents cavitation in the pump caused by air bubbles.

- Low friction characteristics benefit fuel economy even under difficult driving conditions.
- High shear stability maintains lubrication performance during long service intervals and keeps equipment operating efficiency high.

#### SPECIFICATIONS/ APPROVALS

API GL – 4

#### STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

#### HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used products should not be incinerated or disposed of in soil or wastewater channels. Waste oils should be categorized according to the Waste Oil Control Regulation and disposed of through licensed facilities with the specifications defined in this regulation. Please read the Material Safety Data Sheet if necessary.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
Density (20°C, g/cm <sup>3</sup> )	0.855	ASTM D 1298
Kinematic Viscosity (100°C, cSt)	9.0	ASTM D 445
Viscosity Index	125	ASTM D 2270
Pour Point (°C)	-40	ASTM D 97
Flash Point (°C)	215	ASTM D 92

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

00.2025.08.22



**BELGİN**

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.  
Gebze OSB Mah. İhsan Dede Cad.  
No: 125/1, 41400 Gebze, Kocaeli, Turkey  
T +90 262 751 02 92 F +90 262 751 01 98  
info@lubex.com.tr - lubex.com.tr