

LUBEX AGROS UTTO PLUS

HIGH PERFORMANCE TRANSMISSION AND HYDRAULIC OIL

PRODUCT DESCRIPTION

LUBEX AGROS UTTO PLUS is a multi-purpose transmission and hydraulic oil produced by blending high quality base oils and special additives.

APPLICATION/USAGE

It has been developed for use in the transmission, hydraulic system, wet brake, and other auxiliary systems of tractors and construction machinery.

ADVANTAGES/BENEFITS

- Thanks to its excellent viscosity stability, it forms a durable oil film under all kinds of demanding operating temperatures and heavy loads, minimizing wear on the equipment.
- Its superior oxidation stability resists thickening and sludge formation at high operating temperatures, protecting the equipment and enhancing performance during extended operating conditions.
- It provides silent braking comfort in oil bath brake systems thanks to the special friction modifier additives it contains.
- It provides protection against corrosion even under the most challenging road and climate conditions, extending the equipment's lifespan and reducing maintenance costs.
- It more than meets the UTTO oil requirements of various OEMs.

SPECIFICATIONS/APPROVALS

API GL-4
ALLISON: C-2/C-3/C-4
CATERPILLAR TO-2
CNH MAT 3525
EATON VICKERS
FORD: ESN M2C134-A/B/C/D M2C92-A, M2C48A/B
JI CASE: MS 1204-MS 1205-MS 1206-MS 1207-MS 1210
JOHN DEERE: JDM J20A/B/C/D, JDM J14B/C, JDM 21A, JDT 303 Quatrol
Komatsu Dresser B-06-0001 / B-06-0002
KUBOTA UDT
MASSEY FERGUSON: M1135-M1141-M1143-M1145
NEW HOLLAND: FNHA-2-C200A, FNHA-2-C201
WHITE FARM: Q-1826/1802 Type 55/1766/1766-B/1722/1705
VOLVO CE WB-101
ZF TE-ML 03E/05F/06K/17E/21F

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL TEST VALUES	TEST METHOD
SAE Viscosity Class	10W-30	-
Appearance	Clear	-
Density (20°C) (g/cm ³)	0.88	ASTM D 1218
Kinematic Viscosity (100°C, cSt)	9.3-12.5	ASTM D 445
Viscosity Index	140	ASTM D 2270
Flash Point (°C)	220	ASTM D 92
Pour Point (°C)	-33	ASTM D 92

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

00.2025.08.22



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr