

LUBEX AGROS STOU SERIES

SUPER TRACTOR OILS UNIVERSAL

PRODUCT DESCRIPTION

It is a multigrade Super Tractor Oil Universal blended with high quality refined mineral base oils and special additives to provide high oxidation stability, corrosion protection and anti-wear performance.

APPLICATION/USAGE

It is a multi-functional oil which have been specially designed for the lubrication of the engines(including turbo engines), transmissions, hydraulics, wet clutches and oil immersed brakes of the agricultural vehicles.

ADVANTAGES/BENEFITS

- It contains detergent/dispersant additive which provides excellent cleanliness performance to improve engine efficiency and prolong its life.
- It provides high oxidation stability to maintain the operating efficiency of all mechanical components.
- It is suitable for most wet brake systems and ensures optimum performance while minimising brake noise.
- It has a high viscosity index that ensures a durable oil film to prevent wear during cold start-up and high temperature operating conditions.
- It provides excellent anti-corrosion protection for all working parts and components.

SPECIFICATIONS/APPROVALS

Allison C4
API GL-4
API CG-4/CF-4/CF/SF
ACEA E3
John Deere J27
Massey Ferguson M1144, M1145, M1139
MB 227.1
New Holland 8200 9201,2,3
ZF TE ML 06A, B, C, 07B
Sperry Vickers/Eaton I-280-S & M2950S
Sauer Sunstrand/Danfoss Hydro Static Trans Fluid
Ford M2C-159B,C

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES			TEST METHOD
SAE Viscosity Class	10W-30	10W-40	15W-40	-
Kinematic Viscosity (100°C, cSt)	11,6	14,4	14,5	ASTM D 445
Viscosity Index	140	150	130	ASTM D 2270
Flash Point (°C)	210	220	225	ASTM D 92
Pour Point (°C)	-36	-33	-15	ASTM D 97
TBN (mgKOH/g)	10,7	10,7	10,7	ASTM D 2896

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

00.2023.12.01



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr