

LUBEX AGROS UTTO 42 TRACTOR OIL (UTTO)

PRODUCT DESCRIPTION

LUBEX AGROS UTTO 42 formulated with high quality solvent refined paraffinic mineral oil containing extreme pressure additives and friction modifiers for transmissions, final drives and hydraulic systems of farm and industrial tractors and mobile equipment including those with oil immersed disc brakes.

APPLICATION/USAGE

It is recommended for transmissions, hydraulic and power steering systems and fluid immersed brakes in agricultural and industrial tractors and similar mobile equipment.

ADVANTAGES/BENEFITS

- Has high heat resistance and makes lubrication at high temperatures. It provides power transmission at low temperatures.
- Prevents rust and corrosion and reduces any tendency towards the formation of foam which can promote cavitation, noisy pump operation and increased wear.
- Has a high viscosity index value and contains exclusive additives which protects the engine and prolongs its life.
- In virtue of its detergent/dispersant additives, it cleans up the engine.

- Has low oil consumption in virtue of its excellent viscosity control.
- Improves engine performance by providing maximum efficiency.
- Increases engine performance and extends its life.

SPECIFICATIONS/APPROVALS

API GL-4,
Massey Ferguson 1135,
FORD M2C-86-B

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TEST VALUES	TEST METHOD
SAE Viscosity Class	10W-30	
Appearance	Dark Yellow, Clear	-
Kinematic Viscosity (100°C, cSt)	9,3-12,5	ASTM D 445
Viscosity Index	105	ASTM D 2270
Flash Point (°C)	220	ASTM D 92

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

03.2021.03.09



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr