

# LUBEX ANTIFREEZE READY TO USE-56

**RADIATOR FLUID** 

## **PRODUCT DESCRIPTION**

It is a mono-ethylene glycol based concentrated antifreeze formulated with superior anticorrosion, antiwear and antifoam additives to be used in gasoline and diesel engine coolant systems.

# **APPLICATION/ USAGE**

It is suitable to use in gasoline and diesel engines. It is ready to use directly. It is not recommended to use in regions colder than -56°C.

# **ADVANTAGES/ BENEFITS**

- It can be used in radiators for all seasons.
- Compatible with all components of cooling systems including aluminum radiators.
- Due to its special anticorrosion additives protects the copper and brass materials in the engine against corrosion, does not harm the seals.
- Prevents the formation of cracking and other damages caused by expansion in cold climates.
- It is compatible with all sealing components.
- It does not contain any nitrites.

### STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

### **HEALTH AND SAFETY**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TEST VALUES	TEST METHOD
Appearance	Clear	-
Color	Blue	ASTM D 1122
Freezing Point (°C)	-56	ASTM D 1177
Boiling Point (°C)	117	ASTM D 1120
pH Value	7,0 - 11,0	ASTM D 1287

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."



01.2021.07.14

#### BELGIN MADENI YAĞLAR TİC. ve SAN. A.Ş. Gebze OSB Mah. İhsan Dede Cad. No: 125/1, 41400 Gebze, Kocaeli, Turkey T +90 262 751 02 92 F +90 262 751 01 98 info@lubex.com.tr - lubex.com.tr