

LUBEX LONG LIFE ANTIFREEZE READY TO USE-56

RADIATOR FLUID

PRODUCT DESCRIPTION

It is an ethylene glycol based red antifreeze with special organic type corrosion inhibitors, especially designed for vehicles with radiators made of aluminum and its alloys.

APPLICATION/ USAGE

It decreases the freezing point of water in the radiator systems, increases the boiling point. It is recommended to use 4 seasons in radiators made of steel, aluminum and its alloys.

This product is prepared with mixing water to provide the protection up to -56°C in cooling systems. It is ready to use directly. It is not recommended to use in cold areas that are cooler than -56°C.

It should not be mixed with other inorganic antifreeze. In case, the system should be washed with plenty of water.

ADVANTAGES/ BENEFITS

- Has superior additives promoting corrosion protection and minimizing cavitations formed due foam in the system.
- Offers long life protection even under heavy conditions.
- It does not cause any negative effects on the sealing.

- It does not contain any nitrites, boron, phosphorous and silicates.
- Resistant to bacteria production.

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TEST VALUES	TEST METHOD
Appearance	Red, clear	-
Density (g/mL, 15°C)	1,088	ASTM D 1122
Freezing Point (°C)	-56	ASTM D 1177
Boiling Point (°C)	119	ASTM D 1120
pH Value	7,4	ASTM D 1287

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

01.2021.03.30



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr