

LUBEX MITRAS ATF ST DX III

AUTOMATIC TRANSMISSION OIL

PRODUCT DESCRIPTION

It is the semi-synthetic automatic transmission oil produced by blending high quality refined synthetic and mineral base oils and special additives.

APPLICATION/USAGE

It can be used in automatic transmissions of passenger cars and heavy duty vehicles, hydraulic steering and some hydraulic systems.

ADVANTAGES/BENEFITS

- Shows superior performance in hot and cold climatic conditions.
- Thanks to special additives it contains, increases the equipment performance by minimizing wear in automatic transmissions.
- Due to their thermal stability and high oxidation resistance they are long-life products.
- Thanks to the special additives it contains, prevents the formation of sediment and does not foam.
- Reduces maintenance cost and increases the reliability of the gearbox by reducing oil leakage, oil consumption and contamination.
- Provides long-term oil and equipment life with extended oil and filter change intervals.
- Reduces waste disposal costs by minimizing the frequency and amount of oil change due to its long life.

SPECIFICATIONS/APPROVALS

Allison C-4 Fluids
Allison TES, 389
Caterpillar TO-2 Fluids
Ford MERCON
Ford M2C138CJ, M2C 166-H Fluids
GM DEXRON III-H, III-G, III-F, III-E, III-D
MAN 339 Z1 ve V1, Z2 ve V2
MB 236.1, 236.5, 236.6, 236.7
Voith 55,6335 ve 55,6336
Volvo 97340, 97341
ZF TE-ML 02F, 04D, 09, 11A, 14A, 17C

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METODU
Appearance	Red-Bright	-
Density (20°C, g/cm ³)	0,850	ASTM D 1298
Kinematic Viscosity (100°C, cSt)	7,5	ASTM D 445
Viscosity Index	160	ASTM D 2270
Flash Point (°C)	160	ASTM D 92
Pour Point (°C)	-42	ASTM D 97
Foam (93,5°C, Seq. II, ml, max.)	50/0	ASTM D 892
Copper Corrosion (3 h, 100°C, max.)	1b	ASTM D 130

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

03.2021.03.23



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr