

LUBEX MITRAS CVT

HIGH PERFORMANCE CVT TRANSMISSION FLUID

PRODUCT DESCRIPTION

Synthetic automatic transmission fluid designed for continuous variable transmissions (CVT) produced by blending synthetic base oils and special additives.

APPLICATION/USAGE

Suitable for passenger cars with CVT (Continuously Variable Transmission) type transmission systems, especially for vehicles manufactured by Japanese OEMs.

ADVANTAGES/BENEFITS

- Displays superior performance and provides smooth shifting in hot and cold climate conditions.
- With its special additives and superior cold flow performance, it prevents wear during cold start-up of the vehicle and extends the life of the transmission.
- It provides excellent protection against steel-to-steel friction with its special additives and improves vehicle performance.
- Due to its high oxidation resistance and thermal stability, it provides long oil change interval and reduces maintenance costs.
- It prevents the formation of deposits and does not cause foaming. It protects the transmission against corrosion and rust, and also improves the efficiency and reliability of the transmission by preventing oil leakages.
- It minimizes maintenance and waste disposal costs by extending the oil change interval due to its long oil life.

SPECIFICATIONS/APPROVALS

BMW Mini Cooper EZL 799A
Chery CVT
Daihatsu AMMIX CVTF DFE
Dodge / Jeep / Chrysler NS-2
Dodge / Chrysler / Jeep / Mopar CVT+4
GM /Saturn DEX-CVT / GM CVT
Honda HMMF / HCF2 / CVT
Hyundai / Kia CVT-1 / SP III
Mazda JWS 3320
MG Rover EM-CVT
Mini Cooper EZL 799 / EZL 799A / ZF CVT V1
Mitsubishi CVTF-J1 / CVTF-J4 ve -J4+ / SP-III / CVTF ECO J4
Nissan KTF-1 / Nissan NS-1 / NS-2; NS-3
Subaru iCVT / Subaru iCVT F / FG; ECVT; NS-2
Suzuki CVTF TC / CVTF 3320 / CVTF 4401 / NS-2
Suzuki CVT Green 1 / Green 2 / Green 1V
Toyota CVTF TC / CVTF FE
Volvo CVT 4959
VW / Audi TL 521 16 (G 052 516) / TL 521 80 (G 052 180 A2)

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

01.2021.03.23



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
Appearance	Red-Bright	-
Density (15°C, g/cm ³)	0,850	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	7,3	ASTM D 445
Viscosity Index	179	ASTM D 2270
Flash Point (°C)	205	ASTM D 92
Pour Point (°C)	-48	ASTM D 97
Foam (93.5°C, Seq. II, ml, max.)	50/0	ASTM D 892
Brookfield Viscosity (-40°C, mPa.s)	14470	ASTM D 2983
Copper Corrosion (3 h, 100°C)	1b	ASTM D 130

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

01.2021.03.23



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr