

LUBEX PRIMUS C3-LA 5W-40

HIGH PERFORMANCE FULLY SYNTHETIC MOTOR OIL

PRODUCT DESCRIPTION

It is the fully synthetic motor oil developed for new generation, high performance and low emission motors. It is compatible with exhaust emission systems of gasoline, passenger diesel and light commercial vehicles which meet the Euro 4 and 5 emission standard requirements, in particular diesel particulate filter (DPF).

APPLICATION/ USAGE

It is suitable for use in motors of gasoline, passenger diesel and light commercial vehicles that meet the Euro 4 and 5 emission standard requirements. It can be used without any problem in engines of all kinds of modern technology vehicles with direct injection, turbocharged and multi valve.

ADVANTAGES/ BENEFITS

- Produced with mid SAPS (sulfated ash, phosphorus and sulfur) technology for diesel particulate filter (DPF) motors to reduce harmful exhaust emissions. Extends the life of the exhaust emission system, protects the environment.
- Provides excellent engine protection against sediment and soot formation with superior cleaning power.
- It can be used safely in all four seasons by providing constant lubrication in all climate and road conditions. It has low oil consumption because of its excellent viscosity control property.
- Thanks to additives it contains, it prevents wear and corrosion, protects the motor even in the most severe road and climate conditions without pressure

reduction.

- It is produced with Low Friction Technology and thanks to its high viscosity index, it creates a durable oil film at any temperature and minimizes the level of wear occurring during engine start-up and heating.
- It dissolves the soot and dirt formed by combustion in the environment with the help of detergent-dispersing additives in its content and prevents the accumulation of sediment and keeps the engine parts clean.
- Increases motor performance by maximizing fuel efficiency.
- Thanks to its synthetic oils and high oxidation resistance, it has a long service life and long drain interval.

SPECIFICATIONS/ APPROVALS

API SN
ACEA C3

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	5W-40	-
Density (15°C)	0,853	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	14,0	ASTM D 445
Viscosity Index	170	ASTM D 2270
Flash Point (°C)	220	ASTM D 92
Pour Point (°C)	-42	ASTM D 97
TBN (mgKOH/g)	7,1	ASTM D 2896
CCS (-30°C, cP)	6000	ASTM D 5293
Sulphated Ash (%wt)	0,77	ASTM D 874
HTHS (150°C, cP)	3,9	ASTM D 4741

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

04.2021 10.27



BELGiN

BELGiN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr