

LUBEX PRIMUS EC 0W-40

HIGH PERFORMANCE FULLY SYNTHETIC MOTOR OIL

PRODUCT DESCRIPTION

It is formulated by using synthetic base oils and specially selected additive technology. It meets the API SN standards which has been determined as the highest performance level for gasoline motors by American Petroleum Institute (API).

APPLICATION/ USAGE

It has been developed for use in new technology passenger cars. It is suitable for many model vehicles with all natural aspiration, direct injection, turbocharged and multi-valve engines that work with gasoline and diesel.

ADVANTAGES/ BENEFITS

- Minimizes wear with its excellent fluidity properties at the time of first run of engine even at low temperatures,
- Provides excellent engine protection against sediment and soot formation with its superior cleaning power,
- Provides constant lubrication in all climate and road conditions. Therefore it can be used safely in all four seasons,
- Creates a durable oil film at very low or very

high temperatures and protects the engine against corrosion and wear by its special additives.

- It has low oil consumption thanks to its excellent viscosity control,
- Increases the motor performance by ensuring maximum efficiency from fuel.

SPECIFICATIONS/ APPROVALS

API SN

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

| TECHNICAL PROPERTIES | TYPICAL VALUES | TEST METHOD |
|----------------------------------|----------------|-------------|
| SAE Viscosity Class | 0W-40 | - |
| Density (15°C) | 0,846 | ASTM D 4052 |
| Kinematic Viscosity (100°C, cSt) | 13,85 | ASTM D 445 |
| Viscosity Index | 175 | ASTM D 2270 |
| Flash Point (°C) | 220 | ASTM D 92 |
| Pour Point (°C) | -45 | ASTM D 97 |
| TBN (mgKOH/g) | 8,3 | ASTM D 2896 |
| CCS (-35°C, cP) | 6100 | ASTM D 5293 |
| HTHS (150°C, cP) | 3,0 | ASTM D 4741 |

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

03.2021.03.11



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr