

LUBEX PRIMUS MV 10W-60

FULLY SYNTHETIC MOTOR OIL FOR HIGH PERFORMANCE VEHICLES

PRODUCT DESCRIPTION

It is the fully synthetic motor oil which includes high performance synthetic base oils and high technology additives. It has been designed for use at especially motor sports, long mile and high-speed vehicles.

APPLICATION/ USAGE

It has been developed for engines which are required high performance like motor sports and works under high temperature and pressure. It can be used in all types of motor vehicles such as long-mileage, high speed gasoline, passenger diesel and light commercial vehicles. It is suitable for turbocharged, supercharged, petrol and diesel multi-point fuel injection engines.

ADVANTAGES/ BENEFITS

- Provides excellent lubrication performance at high temperatures.
- Particularly recommended for high speed driving conditions such as motor sports.
- Creates excellent oil film thickness for superior protection in high mileage engines.
- Suitable for all driving conditions, especially for sportive driving. Provides the highest level of wear protection for quiet and vibration-free driving.
- Provides high protection for the engine against wear, corrosion and oxidation due to its excellent lubrication under all driving and operating conditions. Therefore it can be used safely in four seasons.
- Provides excellent engine protection against the formation of soot and sediment due to its excellent cleaning power.

- With the help of detergent-dispersing additives it contains, it dissolves the contamination caused by combustion in the environment and prevents accumulation of sediment. Keeps the engine clean and prolongs its life due to ensuring the lubrication channels remain clean.

SPECIFICATIONS/ APPROVALS

API SN/CF
ACEA A3/B4
BMW LL-98
GM LL-B-025
MB 229.3
RENAULT RN 0700, RN 0710
VW 502.00 / 505.00

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	10W-60	-
Density (15°C, g/cm ³)	0,858	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	24,0	ASTM D 445
Viscosity Index	160	ASTM D 2270
Flash Point (°C)	250	ASTM D 92
Pour Point (°C)	-30	ASTM D 97
TBN (mgKOH/g)	10,5	ASTM D 2896
CCS (-25°C, cP)	6700	ASTM D 5293
HTHS (150°C, cP)	5,8	ASTM D 4741

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

03.2021 10.27



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr