

LUBEX ROBUS PRO LA 15W-40**HEAVY DUTY DIESEL ENGINE OIL****PRODUCT DESCRIPTION**

It is a high performance heavy vehicle engine oil, produced with specially selected high quality base oils and additive technology, suitable for use in fleets with large vehicle parks, with certain OEM approvals and specifications. It is suitable for use in vehicles conforming to Euro VI, Euro V, Euro IV, and older emission systems.

APPLICATION/ USAGE

Its primary use is in heavy commercial diesel and gasoline engines. It is especially suitable for vehicles with low emissions, diesel particulate filter (DPF), Euro VI, Euro V and Euro IV engines where Low-SAPS (Low Sulfated Ash, Phosphorus and Sulfur) oils are required. It can also be safely used in older vehicles where the specified performance level is desired, and in construction machinery and equipment operating under low speed / heavy load conditions and using low sulphur content fuel.

ADVANTAGES/ BENEFITS

- Provides constant lubrication for all kinds climate and road conditions so it can be used safely in four seasons,
- Protects the engine against corrosion, oxidation and wear.
- Producing with low friction technology and due to its excellent fluidity and pumpability properties provides maximum protection against wear at the time of first run of engine.
- Helps the protection of diesel particulate filter thanks to its low SAPS (sulfated ash, phosphorus, sulfur) value.
- Has high piston cleaning performance that provides excellent protection against polishing and wearing of cylinder and also provides engine protection even in the presence of soot and other contaminants.

- Has high resistance against thermal degradation and provides continuous protection even in heavy conditions.
- Provides a long life and extends the oil changing periods.

SPECIFICATIONS/ APPROVALS

API CK-4, CJ-4, CI-4 PLUS/SN
ACEA E9
CAT ECF-3
CUMMINS CES 20086
DETROIT DDC 93K222
DEUTZ DQC III-18 LA
FORD WSS-M2C171-F1
MTU TYPE 2.1
MACK EOS 4.5
MAN M 3775
MB 228.31
Renault RLD-3
Volvo VDS-4.5

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

07.2022.02.08

**BELGİN**

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	15W-40	-
Density (15°C, g/cm ³)	0,878	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	14,5	ASTM D 445
Viscosity Index	135	ASTM D 2270
Flash Point (°C)	225	ASTM D 92
Pour Point (°C)	-30	ASTM D 97
TBN (mgKOH/g)	7,4	ASTM D 2896
CCS (-20°C, cP)	6400	ASTM D 5293
Sulphated Ash (%wt)	1,0	ASTM D 874
HTHS (150°C, cP)	4,2	ASTM D 4741

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification,"

07.2022.02.08



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr