

LUBEX ROBUS PRO CNG 15W-40

HIGH PERFORMANCE HEAVY DUTY MOTOR OIL

PRODUCT DESCRIPTION

LUBEX ROBUS PRO CNG 15W-40 is a high performance heavy duty engine oil specially designed for use in compressed natural gas (CNG) and liquefied natural gas (LNG) engines.

APPLICATION/ USAGE

It is a high performance, low ash content engine oil designed for use in heavy commercial vehicles operating with CNG and LNG fuels. It is especially recommended for use in Cummins engines that require CES 20074 specifications.

ADVANTAGES/ BENEFITS

- Owing to specially selected additives, it extends engine life by providing superior protection against wear under harsh conditions.
- It provides superior piston and engine cleaning thanks to the detergent-dispersant additives it contains.
- Its low ash feature reduces the formation of deposits and deposits in the combustion chamber, prolonging valve and spark plug life.
- Thanks to its excellent thermal and oxidation stability, it provides a safe lubrication performance during the oil change period.
- Due to its alkaline additives, it neutralizes harmful acids in the combustion chamber and protects critical parts of the engine against corrosion.

SPECIFICATIONS/ APPROVALS

Cummins CES 20074

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	15W-40	-
Density (15°C) (g/ cm ³)	0,870	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	14,8	ASTM D 445
Viscosity Index	136	ASTM D 2270
Flash Point (°C)	224	ASTM D 92
Pour Point (°C)	-33	ASTM D 97
TBN (mgKOH/g)	5,2	ASTM D 2896
CCS (-20°C, cP)	6043	ASTM D 5293

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

00.2021.08.03



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr